

# »POWRBANK XPRO

## EMISSION-FREE, SILENT POWER

The POWRBANK XPRO energy storage system works with diesel generators to reduce carbon emissions and fuel usage by up to 80%. When used with renewable energy sources, it provides endless hours of zero-emission power.



MODEL	VOLTS	KVA	KWH	PHASE
X90.120/400	400	90	120	3

### POWER

Output (stand alone)	Standby Rating 30 min (kVA) @ 25°C <sup>1</sup>	90
	Prime Rating (kW) @ 25°C / 40°C <sup>1</sup>	72 / 60
	Full Load Current	103.90A per phase
Output (when external source available)	Maximum Load per Phase Before Generator Start Command (kW) <sup>1,2</sup>	20.4 (Immediate Start) 18 (5 mins)
	Maximum Load (all phases) Before Generator Start Command (kW) <sup>5</sup>	53.9 (2 hours)
Combined System Output	Continuous Pass Through per phase (External Source Only) (A)	200
	Max Combined Output per phase (External Source + HES) (A) <sup>1</sup>	250
	Max Power Assist (kVA) <sup>1</sup>	72
Input/Output	AC Input Voltage Range (V)	400 (320 - 460)
	AC Output Voltage - 50 Hz (V)	400
	Input Connections	125A 400V & 16A 230V CEE-Forms, 400V BusBar
	Output Connections	125A 400V & 16A 230V CEE-Form & 400V BusBar
	Protection	Overload, Overheat, Short Circuit, Earth Fault

### STORAGE

Type	LFP (Lithium Iron Phosphate)
Nominal Capacity @ 25°C (kWh)	127.9
Charge Time (hours) @ 25°C <sup>3</sup>	2h 45min
Maximum System Efficiency @ 25°C	90%
Battery Management System	Industrial Grade Intelligent Passive BMS Optimised for HES Applications
Expected Cycle Life (To 80% Original Capacity)	6,000
Maintenance Charge Cycle	≤ 4 weeks

### CONTROL

Control Panel	ADVANTAGE by POWR2, 10" Touch Screen Control Module and Energy Management Cloud
Temperature Control	Analogue Voltage Controlled Forced Air Cooling
Remote Generator Start	Dry Contact Relay
Remote Communication	3G/4G Dual SIM Modem/Router, POWR2 Portal

### ENVIRONMENTAL

Water/Ingress Protection Rating	IP55
Operating Temperature Range (°C) <sup>4</sup>	-12 to +50
Sound Level (dBA) @ 0% / 100% Fan Speed	Acoustic Pressure @ 3m: 0 / 66

### MECHANICAL

Dimensions L x W x H (mm / inches)	2250 x 1398 x 2062 / 88.6 x 55.0 x 81.2
Weight (kg/lbs)	2800 / 6173
Lift Points	Dual Rotable Lifting Ring (2 Point Lift), Forklift Pockets, Lift & Drag Skid

<sup>1</sup> Depending on battery bank SoC <sup>2</sup> Multiple start conditions available upon request for bespoke applications. <sup>3</sup> Charge time dependent on available power of external source and operating temperature. <sup>4</sup> When the internal battery temperature reaches below 2°C or above 38°C, the charge current is reduced to 0.05C to protect the batteries. <sup>5</sup> Without exceeding Max. Load per Phase. Document updated August 2024. While POWR2 aims to ensure all documentation is accurate, no responsibility will be accepted for errors or omissions. This document is not intended to be contractual. © POWR2 2024 Datasheet X90.120-400\_V4.1